



Little Village High School – Chicago, IL

## **Structural Glazed Cove Base Units**

*For the Base Course of Your Walls*

---


Structural Glazed Cove Base units combine aesthetics with durability for practical applications in schools, hospitals, and other commercial projects. Since these units are made of ceramic glazed masonry, they are ideal for high-traffic areas with sanitary requirements. Available in an array of beautiful colors, they are the perfect addition to carpet, terrazzo, marble, linoleum, or concrete flooring.

**Elgin Butler Company**


365 FM 696, Elgin, Texas 78621 | p (512) 285-3356 | f (512) 281-2487 | [contact@elginbutler.com](mailto:contact@elginbutler.com) | [www.elginbutler.com](http://www.elginbutler.com)

## Cove Base Product Information

• **Recessed Cove Base:** Typically used with terrazzo flooring or quarry tile, these units have a 1/2" lip that allows for the finished floor to be placed after the walls are installed. The flooring material then fills up to the 1/2" lip area leaving a sanitary transition between the flooring and walls.



• **Non-Recessed Cove Base:** Typically used with a concrete slab and a thin type of finished flooring material, such as vinyl or a painted surface.



• **Straight Base:** Typically used when a cove base is not required; stretcher unit. Thickness are available in 2", 4", 6", or 8".

• **Shapes:** Furnished as shown on the plans in accordance with the current standard production of the manufacturer. All external corners shall be bullnose unless otherwise noted. Internal corners shall be square unless otherwise noted.



Jones Technical High School – Chicago, IL  
Cove Base Corner

• **Dimensions in Inches:**

**Nominal 2" and 4" Thickness x Height x Length**

**Series/Sizes**

- 4W 8-Square: 7-5/8 x 7-5/8
- 6T: 5 x 11-11/16
- 8W: 7-5/8 x 15-5/8

### SPECIFICATION

Structural Glazed Tile shall be ceramic glazed fire clay units as manufactured by Elgin Butler Company and shall conform to ASTM C-126, Grade S, Type I & II, selected from the manufacturer's standard colors. Sized for 3/8" mortar joints (except 6T sized for 5/16" mortar joints).

06075000-010